


JBL

PROFESSIONAL

VTX SERIES
SYSTEM SOLUTIONS

VTX A12 | Preset Library



General Information

VTX A12 Preset Library

Version: R1.1

Distribution Date: 04/17/2017

Copyright © 2017 by Harman International; all rights reserved

JBL Professional

8500 Balboa Blvd

Northridge, CA 91329

USA

Preset Release History

Release 1.1:

- Initial VTX A12 Preset release

Preset Name Description


- FL (FILL) = Preset nominal frequency response suitable for front fill use
- Full Range Presets = The full-range preset for **A12** extend the system frequency response down to **45Hz**
- 60 = Refers to an 60Hz high-pass or low-pass filter
- 80 = Refers to an 80Hz high-pass or low-pass filter
- REAR = Cardioid preset to be used for the rear facing subwoofer enclosure

Notes

- The most up to date versions of all VTX presets are always included in the latest version of JBL's Performance Manager™ software.
- Make sure the latest Crown Audio I-Tech HD firmware is used
- Arbitrary preset combinations can be created using JBL's HiQNet Performance Manager™ control software
- For more information on preset selection refer to the VTX A12 User Manual

Crown Audio I-Tech 4x3500HD


Device File: VTX A12 R1.1.0.I-TECH4x3500HD.Device



			CH 1	CH 2	CH 3	CH 4
VTX A12 FILL Presets						
VTX A12 FL	2	VTX A12 Fill, Full Range	A12 LF FL	A12 LF FL	A12 MF FL	A12 HF FL
VTX A12 FL 80	3	VTX A12 Fill, HPF: 80Hz	A12 LF FL 80	A12 LF FL 80	A12 MF FL 80	A12 HF FL 80
VTX A12						
VTX A12	5	VTX A12 Preset for use in arrays, Full Range	A12 LF	A12 LF	A12 MF	A12 MF
VTX A12 80	6	VTX A12 Preset for use in arrays, HPF: 80Hz	A12 LF 80	A12 LF 80	A12 MF 80	A12 HF 80
VTX S28						
VTX S28 60	8	VTX S28, LPF: 60Hz	S28 60	S28 60	S28 60	S28 60
VTX S28 60 REAR	9	VTX S28, LPF: 60Hz, Rear Firing for Cardioid	S28 60 REAR	S28 60 REAR	S28 60 REAR	S28 60 REAR
VTX S28 80	10	VTX S28, LPF: 80Hz	S28 80	S28 80	S28 80	S28 80
VTX S28 80 REAR	11	VTX S28, LPF: 80Hz, Rear Firing for Cardioid	S28 80 REAR	S28 80 REAR	S28 80 REAR	S28 80 REAR
VTX G28						
VTX G28 60	13	VTX G28, LPF: 60Hz	G28 60	G28 60	G28 60	G28 60
VTX G28 60 REAR	14	VTX G28, LPF: 60Hz, Rear Firing for Cardioid	G28 60 REAR	G28 60 REAR	G28 60 REAR	G28 60 REAR
VTX G28 80	15	VTX G28, LPF: 80Hz	G28 80	G28 80	G28 80	G28 80
VTX G28 80 REAR	16	VTX G28, LPF: 80Hz, Rear Firing for Cardioid	G28 80 REAR	G28 80 REAR	G28 80 REAR	G28 80 REAR

Crown Audio I-Tech 1 2000HD

Device File: VTX A12 R1.1.O.I.TECHHD.Device



			CH 1	CH 2
VTX A12 FILL Presets				
VTX A12 FL MF/HF	2	VTX A12 Fill, Full Range, MF HF	A12 MF FL	A12 HF FL
VTX A12 FL LF/LF	3	VTX A12 Fill, Full Range, LF/LF	A12 LF FL	A12 LF FL
VTX A12 FL 80 MF/HF	4	VTX A12 Fill, HPF: 80Hz, MF/HF	A12 MF FL 80	A12 HF FL 80
VTX A12 FL 80 LF/LF	5	VTX A12 Fill, HPF: 80Hz, LF/LF	A12 LF FL 80	A12 LF FL 80
VTX A12				
VTX A12 MF/HF	7	VTX A12, Full Range, MF/HF	A12 MF	A12 HF
VTX A12 LF/LF	8	VTX A12, Full Range, LF/LF	A12 LF	A12 LF
VTX A12 80 MF/HF	9	VTX A12, HPF: 80Hz, MF/HF	A12 MF 80	A12 HF 80
VTX A12 80 LF/LF	10	VTX A12, HPF: 80Hz, LF/LF	A12 LF 80	A12 LF 80
VTX S28				
VTX S28 60	12	VTX S28, LPF: 60Hz	S28 60	S28 60
VTX S28 60 REAR	13	VTX S28, LPF: 60Hz, Rear Firing for Cardioid	S28 60 REAR	S28 60 REAR
VTX S28 80	14	VTX S28, LPF: 80Hz	S28 80	S28 80
VTX S28 80 REAR	15	VTX S28, LPF: 80Hz, Rear Firing for Cardioid	S28 80 REAR	S28 80 REAR
VTX G28				
VTX G28 60	17	VTX G28, LPF: 60Hz	G28 60	G28 60
VTX G28 60 REAR	18	VTX G28, LPF: 60Hz, Rear Firing for Cardioid	G28 60 REAR	G28 60 REAR
VTX G28 80	19	VTX G28, LPF: 80Hz	G28 80	G28 80
VTX G28 80 REAR	20	VTX G28, LPF: 80Hz, Rear Firing for Cardioid	G28 80 REAR	G28 80 REAR